DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D350-689 REV. A

REF TCCA STC: SH02-33 REF FAA STC: SR01620NY REF EASA STC: EASA.IM.R.S.01453 REF BRAZILIAN STC: 2005S03-09

PURPOSE:

TO PROVIDE AN OPTIONAL CONTROL GUARD KIT TO BE INSTALLED ON THE D350-689-011/-021 DUAL HIGH BACK SEAT INSTALLATIONS.

CHANGE:

OPTIONAL D350-689-019 CONTROL GUARD KIT ADDED AS DETAILED BELOW. WHEN INSTALLING THE AN4 BOLTS IN THE DART SEAT, DRILL QTY (2) Ø0.257" HOLES PER INSTRUCTIONS (SEE SHEET 2 DETAIL A OF THIS SERVICE INSTRUCTION FOR REFERENCE).

Qty	Qty	Qty	Qty	Qty	Qty	Qty	Part Number	Description	
-011	-013	-019	-021	-023	-041	-043			
Х							D350-689-011	DUAL HIGH BACK SEAT INSTALLATION, LH	
1	Х						D350-689-013	FLOOR PROVISIONS KIT	
		Х					D350-689-019	CONTROL GUARD KIT	
			Х				D350-689-021	DUAL HIGH BACK SEAT INSTALLATION, LH (REF DSI 9419)	
			1	X			D350-689-023	ENERGY ATTENUATING FLOOR PROVISION KIT (REF DSI 9419)	
1				· · · · · ·	Х		D350-689-041	DUAL HIGH BACK SEAT ASSEMBLY	
			1			Х	D350-689-043	DUAL HIGH BACK SEAT ASSEMBLY (REF DSI 9419)	
				L				<u> </u>	
				F			50004.6	lozpi g	
		3					D3084-3	STRUT	
		2					NAS43DD4-46N	SPACER	
		1					AN4-12A	BOLT	
		1					AN4-20A	BOLT	
		2					MS21042-4	NUT (OR MS24042L4)	
		8					NAS1149D0416J	WASHER	
								TA TO THE TOTAL TO THE TANK TH	

INSTRUCTIONS:

- 1. LOCATE LOWER HOLE (SEE FIGURE 1 SHEET 2) AND DRILL Ø0.257" HOLE.
- 2. USING STRUT P/N D3084-3 AS TEMPLATE, TEMPORARILY FASTEN TO LOWER HOLE, LOCATE UPPER HOLE ON CENTER LINE OF TUBE. REF FIGURE 1.
- 3. DRILL Ø0.257" HOLE.
- 4. REMOVE BURRS AND SHARP EDGES ON BOTH HOLES AND TOUCH UP PER ICA-D350-689 CHAPTER 5.2 SECTION 8.
- 5. INSTALL STRUT USING HARDWARE SHOWN. TORQUE FASTENERS TO 50-70 in-lbs.

LONGER AN4 BOLTS ARE ACCEPTABLE TO ENSURE A MINIMUM OF 1.5-2 THREADS IN SAFETY.

WEIGHT AND BALANCE:

Installation	Weight	LATERAL		LONGITUDINAL	
installation		Arm	Moment	Arm	Moment
D350-689-019 CONTROL GUARD	0.5 lb	-9.0 in	- 4.5 in-lb	60.7 in	30 in-lb
KIT. (Seat's Fwd position)	0.23 kg	-0.23 m	-0.05 m-kg	1.54 m	0.35 m-kg
D350-689-019 CONTROL GUARD	0.5 lb	-9.0 in	- 4.5 in-lb	64.7 in	32 in-lb
KIT. (Seat's Aft position)	0.23 kg	-0.23 m	-0.05 m-kg	1.64 m	0.38 m-kg

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01


BY: D. SHEPHERD (DE # 02)


DATE: 10.04.01

CERT. NO.: SH02-33


ISSUE NO.: 1

Α	NEW IS	ISSUE.			10.04.01	
REV.		DESCRIPTION			DATE	
DESIGN		1	DART AEROSP	ACE	LTD	
DRAWN		18	HAWKESBURY, ONTAR			
CHECKED		OP	DRAWING NO.		REV. A	
MFG. AF	PR.	N/A	DSI 9493		SHEET 1 OF 2	
APPRO\	VED	TW T	TITLE		SCALE	
DE APP	R.	##	INSTALLATION OF CONTRO	OL GU/	ARD NTS	
DATE	10.0	4.01	COPYRIGHT © 2010 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WITTEN PERINSSION FROM DART AEROSPACE LTD.			





SECTION VIEW A-A ROTATED



SECTION VIEW B-B ROTATED

FIGURE 1 D350-689-019 CONTROL GUARD KIT (LOOKING OUTBOARD)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

BY: D. SHEPHERD (DE # 02)

DATE: 10.04.01

CERT. NO.: SH02-33

ISSUE NO.: 1

DESIGN	8	DART AEROSP	ACE LTD		
DRAWN	180	HAWKESBURY, ONTARIO, CANADA			
CHECKED	a	DRAWING NO.	REV. A		
MFG. APPR.	N/A	DSI 9493	SHEET 2 OF 2		
APPROVED	WA	TITLE	SCALE		
DE APPR.		INSTALLATION OF CONTR	OL GUARD NTS		
DATE 10.0	4.01	COPYRIGHT © 2010 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND COMPREHAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR MY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.			